

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

EVO-STIK HARD AND FAST EPOXY PUTTY

Supercedes date 27-Feb-2023

Revision date 22-Apr-2025 Revision Number 2.02

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name EVO-STIK HARD AND FAST EPOXY PUTTY

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Filler

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

Skin irritation	Category 2 - (H315)
Eye irritation	Category 2 - (H319)
Skin sensitisation	Category 1 - (H317)
Hazardous to the aquatic environment - chronic	Category 3 - (H412)

2.2. Label elements

Contains Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW; Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2.2-bis(hydroxymethyl)1,3-propanediol (4:1), 2-hydroxy-3-mercaptoppropyl ether



United Kingdom - BE Page 1 / 12

EVO-STIK HARD AND FAST EPOXY PUTTY

Supercedes date 27-Feb-2023

Revision date 22-Apr-2025 Revision Number 2.02

Signal word

Warning

Hazard statements

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P273 - Avoid release to the environment

P280 - Wear protective gloves and eye/face protection

P302 + P352 - IF ON SKIN: Wash with plenty of water and soap

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable

2.3. Other hazards

No information available.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight- %	REACH registration number	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	concentration	M-Factor	M-Factor (long-ter m)	Notes
Bisphenol-A-Epichlor hydrin Epoxy resin <= 700 MW 25068-38-6	10 - <20	01-2119456619 -26-xxxx	500-033-5	Skin Irrit. 2 (H315) Skin Sens. 1 (H317) Eye Irrit. 2 (H319) Aquatic Chronic 2 (H411)	C>=5%	-	-	-
Poly[oxy(methyl-1,2- ethanediyl)], a-hydro-w-hydroxy-, ether with 2.2-bis(hydroxymeth yl)1,3-propanediol (4:1), 2-hydroxy-3-mercapt oppropyl ether 72244-98-5		Exempt	615-735-8	Skin Sens. 1B (H317) Aquatic Chronic 3 (H412)	-		1	1

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

United Kingdom - BE Page 2 / 12

EVO-STIK HARD AND FAST EPOXY PUTTY

Supercedes date 27-Feb-2023

Revision date 22-Apr-2025 Revision Number 2.02

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg		Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Bisphenol-A-Epichlorhy drin Epoxy resin <= 700 MW		25068-38-6	1	-	-	-	-
Poly[oxy(methyl-1,2-eth anediyl)], a-hydro-w-hydroxy-, ether with 2.2-bis(hydroxymethyl) 1,3-propanediol (4:1), 2-hydroxy-3-mercaptop propyl ether		72244-98-5	-	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and

persists.

Skin contact May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see

a doctor. Wash off immediately with soap and plenty of water for at least 15 minutes.

Ingestion Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce

vomiting. Call a doctor.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section

8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Itching. Rashes. Hives. May cause redness and tearing of the eyes. Burning sensation.

Effects of Exposure No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors May cause sensitisation in susceptible persons. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

United Kingdom - BE Page 3 / 12

EVO-STIK HARD AND FAST EPOXY PUTTY

Supercedes date 27-Feb-2023

Revision date 22-Apr-2025 Revision Number 2.02

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

Unsuitable extinguishing media Full water jet. Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical

Product is or contains a sensitiser. May cause sensitisation by skin contact.

Carbon oxides. Hydrogen chloride. Sulphur oxides. Silicon dioxide. **Hazardous combustion products**

5.3. Advice for firefighters

precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal Personal precautions

protective equipment as required. Evacuate personnel to safe areas. Keep people away

from and upwind of spill/leak.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so.

6.3. Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice. Avoid contact Advice on safe handling

with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product.

Take off contaminated clothing and wash it before reuse.

General hygiene considerations Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this

product. Avoid contact with skin, eyes or clothing.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

United Kingdom - BE Page 4 / 12

EVO-STIK HARD AND FAST EPOXY PUTTY Supercedes date 27-Feb-2023

Revision date 22-Apr-2025 Revision Number 2.02

Keep out of the reach of children.

7.3. Specific end use(s)

Specific use(s)

Filler.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom
Talc	=	TWA: 1 mg/m³; respirable dust
14807-96-6		STEL: 3 mg/m³; respirable dust

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)				
Bisphenol-A-Epichlorhydrin	Epoxy resin <= 700 MW (25	6068-38-6)		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker Short term Systemic health effects	Dermal	8.33 mg/kg bw/d		
worker Long term Systemic health effects	Dermal	8.33 mg/kg bw/d		
worker Short term Systemic health effects	Inhalation	12.25 mg/kg bw/d		

Derived No Effect Level (DNEL)				
Bisphenol-A-Epichlorhydrin	n Epoxy resin <= 700 MW (25	068-38-6)		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
Consumer Short term Systemic health effects	Dermal	3.571 mg/kg bw/d		
Consumer Short term Systemic health effects	Oral	0.75 mg/kg bw/d		
Consumer Long term Systemic health effects	Dermal	3.571 mg/kg bw/d		
Consumer Long term Systemic health effects	Oral	0.75 mg/kg bw/d		

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)

United Kingdom - BE Page 5 / 12

EVO-STIK HARD AND FAST EPOXY PUTTY

Supercedes date 27-Feb-2023

Revision date 22-Apr-2025 Revision Number 2.02

Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW (25068-38-6)				
Environmental compartment	Predicted No Effect Concentration (PNEC)			
Freshwater	0.006 mg/l			
Marine water	0.0006 mg/l			
Freshwater sediment	0.996 mg/l			
Marine sediment	0.0996 mg/l			
Soil	0.196 mg/l			

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Hand protection

Tight sealing safety goggles. Eye protection must conform to standard EN 166. Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. Gloves should be

replaced regularly and if there is any sign of damage to the glove material.

Skin and body protection Suitable protective clothing.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical stateSolidAppearancePasteColourGrey Black

Odour Sulphurous. Pungent.

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

Melting point / freezing pointNo data availableNone knownInitial boiling point and boilingNo data availableNone known

range

Flammability No data available None known Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Flash pointNo data availableNone knownAutoignition temperatureNo data availableNone known

Decomposition temperature 150 °C

pH No data available Not applicable.
pH (as aqueous solution) No data available None known
Kinematic viscosity No data available None known

Dynamic viscosity

No data available
Water solubility

Insoluble in water.

Solubility(ies)No data availableNone knownPartition coefficientNo data availableNone knownVapour pressureNo data availableNone known

Relative density 2.25

Bulk density
No data available
Liquid Density
No data available

Relative vapour density

No data available

None known

Particle characteristics

Particle SizeNo information availableParticle Size DistributionNo information available

9.2. Other information

Solid content (%) No information available

United Kingdom - BE Page 6 / 12

EVO-STIK HARD AND FAST EPOXY PUTTY

Supercedes date 27-Feb-2023

Revision date 22-Apr-2025 Revision Number 2.02

VOC content No data available

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid None known based on information supplied.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye

irritation. (based on components). May cause redness, itching, and pain.

Skin contact May cause sensitisation by skin contact. Specific test data for the substance or mixture is

not available. Repeated or prolonged skin contact may cause allergic reactions with

susceptible persons. (based on components). Causes skin irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhoea.

United Kingdom - BE Page 7 / 12

EVO-STIK HARD AND FAST EPOXY PUTTY

Supercedes date 27-Feb-2023

Revision date 22-Apr-2025 Revision Number 2.02

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes.

Acute toxicity

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral) >2000 mg/kg
ATEmix (dermal) >2000 mg/kg
ATEmix (inhalation-gas) >20000 ppm
ATEmix (inhalation-dust/mist) >5 mg/l
ATEmix (inhalation-vapour) >20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Bisphenol-A-Epichlorhydrin	LD50 (Rattus) > 2000 mg/kg	>2000 mg/Kg (Rattus)	-
Epoxy resin <= 700 MW	OECD 420		

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicityBased on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties Based on available data, the classification criteria are not met.

United Kingdom - BE Page 8 / 12

EVO-STIK HARD AND FAST EPOXY PUTTY

Supercedes date 27-Feb-2023

Revision date 22-Apr-2025 Revision Number 2.02

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
	plants		microorganisms			(long-term)
Bisphenol-A-Epichlorhy	EC50 (72h) = 9.4	1.2 mg/l 96Hr	-	2.7 mg/l 48hr		
drin Epoxy resin <= 700	mg/L	(Oncorhynchus		Daphia Magna		
MW	(Scenedesmus	mykiss)				
25068-38-6	capricornutum)					
	EPA-660/3-75-0					
	09					

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient	
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	3.26	

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment Based on available data, the classification criteria are not met.

,,	
Chemical name	PBT and vPvB assessment
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	Not PBT/vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties Based on available data, the classification criteria are not met.

12.7. Other adverse effects

Other adverse effects No information available.

PMT or vPvM propertiesBased on available data, the classification criteria are not met.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

United Kingdom - BE Page 9 / 12

EVO-STIK HARD AND FAST EPOXY PUTTY

Supercedes date 27-Feb-2023

Revision date 22-Apr-2025 Revision Number 2.02

Waste from residues/unused

products

Dispose of in accordance with local regulations. Dispose of waste in accordance with

environmental legislation.

Contaminated packaging Do not reuse empty containers.

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number Not regulated 14.2 UN proper shipping name Not regulated 14.3 Transport hazard class(es) Not regulated Not regulated 14.4 Packing group 14.5 Environmental hazards Not applicable

14.6 Special precautions for user

Special Provisions None

IMDG

14.1 UN number or ID number Not regulated 14.2 UN proper shipping name Not regulated 14.3 Transport hazard class(es) Not regulated 14.4 Packing group Not regulated NΡ

14.5 Marine pollutant

14.6 Special precautions for user

Special Provisions None

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number Not regulated 14.2 UN proper shipping name Not regulated 14.3 Transport hazard class(es) Not regulated 14.4 Packing group Not regulated 14.5 Environmental hazards Not applicable

14.6 Special precautions for user

Special Provisions None

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

United Kingdom - BE Page 10 / 12

EVO-STIK HARD AND FAST EPOXY PUTTY

Supercedes date 27-Feb-2023

Revision date 22-Apr-2025 Revision Number 2.02

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Ozone-depleting substances (ODS) regulation (EC) 2024/590

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of any hazard and/or precautionary statements referred to under Sections 2-15

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H411 - Toxic to aquatic life with long lasting effects H412 - Harmful to aquatic life with long lasting effects

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value Sk* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

ADR European Agreement concerning the International Carriage of Dangerous Goods by

Road

IMDGInternational Maritime Dangerous Goods (IMDG)IATAInternational Air Transport Association (IATA)

United Kingdom - BE Page 11 / 12

EVO-STIK HARD AND FAST EPOXY PUTTY Supercedes date 27-Feb-2023

Revision date 22-Apr-2025 Revision Number 2.02

RID Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 22-Apr-2025

Indication of changes

Revision Note Not applicable.

Training Advice No information available Further information No information available

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

United Kingdom - BE Page 12 / 12